

Gastronorm — TG4 EP PA TN

Catering



Technical data

Gross volume	545 lt
Working temperature	0+8 °C
Motor type	Remote
Refrigerant	R452A
Cooling power	482 W (-10°C / +45°C)
Absorption	204 W
Voltage/Frequency	230V/1~/50Hz
Climate class	5 / (40°C 40%)

Energy data (UE Reg. 2015/1094)

Type	Unenforceable regulation
------	--------------------------

Refrigeration details

Refrigeration unit	Remote with possibility to get as optional protection cover
Evaporator	With cathaphoresis anti-corrosion treatment
Defrost	Automatic by air
Condensate evaporation	Automatic by electric heater

Construction details

Product dimensions WxDxH	1972x700x950
Packaging dimensions WxDxH	2035x750x1070
Gross weight	192 Kg
Worktop	Sturdy and resistant stainless steel AISI 304 worktop. Supplied with splashback (h 10 cm)
Structure	Stainless steel AISI 304 monocoque
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel
Insulation thickness	50 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Inner corners	Rounded for an easy cleaning
Door	4 Self-closing doors with 120° door stop, reversibles on site
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	AISI 304 stainless steel, height adjustable (135mm-230mm)

Functions

Control panel	Compact, simple and intuitive touch screen display. Tilted control panel
---------------	--

Accessories

No. included accessories	4 - Plastic-coated grid GN 1/1 530x325 mm 4 - Pair of runners for grid 530x325 mm
--------------------------	--

Remote unit data

Refrigerant gas for remote motor unit	Set up for R452A
---------------------------------------	------------------

Versions

Versions	Power supply frequency 60Hz
----------	-----------------------------