

Snack —

TS4 P SP BT

Catering



Technical data

Gross volume	473 lt
Working temperature	-15-22 °C
Motor type	Plug-in
Refrigerant	R290
Cooling power	568 W (-25°C / +45°C)
Absorption	616 W
Voltage/Frequency	230V/1~/50Hz
Climate class	5 / (40°C - 40%)

Energy data (UE Reg. 2015/1094)

Type	This equipment is intended for use in ambient temperatures up to 40°C
------	---

Refrigeration details

Refrigeration unit	Tropicalized and easy extractable monoblock unit to guarantee reliability and performance at 43°C. Equipped with low consumption electronic fan motors
Refrigerant charge	95 gr
Evaporator	With cataphoresis anti-corrosion treatment
Defrost	Automatic by hot gas for a shorter cycle and less thermal shocks
Condensate evaporation	Automatic through anti-corrosion treated compressor coil

Construction details

Product dimensions WxDxH	2276x600x810
Packaging dimensions WxDxH	2345x650x940
Gross weight	158 Kg
Worktop	Without worktop
Structure	Stainless steel AISI 304 monocoque
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel
Insulation thickness	50 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Inner corners	Rounded for an easy cleaning
Door	4 Self-closing doors with 120° door stop, reversibles on site
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	AISI 304 stainless steel, height adjustable (135mm-230mm)

Functions

Control panel	Compact, simple and intuitive touch screen display. Tilted control panel
---------------	--

Accessories

No. included accessories	4 - Plastic-coated grid 430x325 mm 4 - Pair of runners for grid 430x325 mm for counters (depth 600 mm)
--------------------------	---

Versions

Versions	Power supply frequency 60Hz
----------	-----------------------------