

# Pizza — TP4 P SP TN

Catering



## Technical data

Gross volume	609 lt
Working temperature	0+8 °C
Motor type	Plug-in
Refrigerant	R290
Cooling power	369 W (-10°C / +45°C)
Absorption	263 W
Voltage/Frequency	230V/1~/50Hz
Climate class	5 / ( 40°C - 40%)

## Energy data (UE Reg. 2015/1094)

Type	This equipment is intended for use in ambient temperatures up to 40°C
------	---

## Refrigeration details

Refrigeration unit	Tropicalized and easy extractable monoblock unit to guarantee reliability and performance at 43°C. Equipped with low consumption electronic fan motors
Refrigerant charge	90 gr
Evaporator	With cataphoresis anti-corrosion treatment
Defrost	Automatic by air
Condensate evaporation	Automatic through anti-corrosion treated compressor coil

## Construction details

Product dimensions WxDxH	2500x800x860
Packaging dimensions WxDxH	2550x850x1000
Gross weight	187 Kg
Worktop	Without worktop
Structure	Stainless steel AISI 304 monocoque
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel
Insulation thickness	60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Inner corners	Rounded for an easy cleaning
Door	4 Self-closing doors with 105° door stop, reversibles on site
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	AISI 304 stainless steel, height adjustable (135mm-230mm)

## Functions

Control panel	Compact, simple and intuitive touch screen display. Tilted control panel
---------------	--

## Accessories

No. included accessories	4 - Plastic-coated grid EN 600x400 mm 4 - Pair of runners for grid EN 600x400 mm
--------------------------	---

## Versions

Versions	Power supply frequency 60Hz
----------	-----------------------------