

Food Preparation —

TF3 P K

Catering



Technical data

Gross volume	609 lt
Working temperature	0+8 °C
Motor type	Plug-in
Refrigerant	R290
Cooling power	369 W (-10°C / +45°C)
Absorption	263 W
Voltage/Frequency	230V/1~/50Hz

Refrigeration details

Refrigeration unit	Tropicalized and easy extractable monoblock unit. Equipped with low consumption electronic fan motors
Refrigerant charge	90 gr
Evaporator	With cataphoresis anti-corrosion treatment
Defrost	Automatic by air
Condensate evaporation	Automatic through anti-corrosion treated compressor coil

Construction details

Product dimensions WxDxH	1970x800x900
Packaging dimensions WxDxH	2020x850x1070
Gross weight	170 Kg
Worktop	Sturdy and resistant stainless steel AISI 304 worktop with hole for GN 1/3 containers. Supplied with lid to guarantee food safety
Structure	Stainless steel AISI 304 monocoque
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel
Insulation thickness	60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Inner corners	Rounded for an easy cleaning
Door	3 Self-closing doors with 105° door stop, reversibles on site
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	AISI 304 stainless steel, height adjustable (135mm-230mm)

Functions

Control panel	Compact, simple and intuitive touch screen display. Tilted control panel
---------------	--

Accessories

No. included accessories	3 - Plastic-coated grid EN 600x400 mm 3 - Pair of runners for grid EN 600x400 mm
--------------------------	---

Versions

Versions	Power supply frequency 60Hz
----------	-----------------------------