

Talent —

TA 6T MF BK EP

Catering



Technical data

Gross volume	159 lt
Working temperature	-40+85°C
Humidity range	55%-95%
Performance from +90°C to +3°C	21 Kg
Performance from +90°C to -18°C	15 Kg
Motor type	Remote
Refrigerant	R452A
Cooling power	1748 W (-10°C / +40°C)
Absorption	935 W
Voltage/Frequency	230V/1~/50Hz

Refrigeration details

Refrigeration unit	Remote with possibility to get as optional protection cover
Evaporator	Conceived to provide the maximum exchange surface and to ensure optimal performance. Equipped with cataphoresis anti-corrosion treatment and door that can be opened for an easy cleaning
Defrost	Manual by air. The equipment can work for 24 hours avoiding ice formation on the evaporator
Condensate evaporation	Through easy extractable condensation collector tray (for installations without water drain system)

Construction details

Product dimensions WxDxH	800x750x840
Packaging dimensions WxDxH	870x840x980
Gross weight	89 Kg
Worktop	Stainless steel AISI 304 worktop (4 cm thickness) reinforced to carry up the weight of an oven
Structure	Stainless steel AISI 304 monocoque conceived with an innovative and functional design
External/Internal material	Inside and outside in stainless steel AISI 304; motor unit compartment and bottom in colaminated steel
Insulation thickness	60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Door	1 Self-closing door right hinged, not reversible on site
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	AISI 304 stainless steel, height adjustable (45mm-60mm)
Nebulizer	As standard (water connection required)

Functions

Control panel	7" touch screen graphic display
Open door alarm	Visual and acoustic
Functions	Soft and hard blast chilling, soft and hard blast freezing, slow cooking, retarder proving, thawing, +65°C holding, automatic end cycle holding, multilevel continous cycle, special cycles: fish sanitisation, chocolate crystallization, yoghurt, dessication, high and low pasteurisation, pre-loaded recipes, 100 customizable recipes, HACCP alarms
Languages	Italian, English, French, German, Spanish, Portuguese, Russian
Probe	Needle probe with precision finish to facilitate extraction from the frozen product. Temperature detection through 3 sensors and automatic recognition of the probe inserted in the food
Connection	As optional: Remote access through serial interface. Via APP (only Android) it is possible to monitor HACCP traceability, appliance operation and parameters. Graphic and as CVS file export of registered data. Email sending of alarms notification

Accessories

Anti-scale system	BRITA filter (head + cartridge) to reduce limescale in drinking water
No. included accessories	6 - Pair of runners for GN 1/1 and EN 600x400 mm 1 - Purity C Filter Head 1 - Brita Purity C50 filter cartridge (up to 960 litres water filtration capacity with carbonate hardness of 10°dH)

Remote unit data

Refrigerant gas for remote motor unit	Set up for R452A
---------------------------------------	------------------

Versions

Versions	Water cooling unit/ Power supply frequency 60Hz
----------	---