

# Performance — PF 700 P BT

Catering

-



#### **Technical data**

630 lt
-15-22 °C
Plug-in
R290
568 W (-25°C / +45°C)
564 W
230V/1~/50Hz
5 / ( 40°C - 40%)

# Energy data (UE Reg. 2015/1094)

Туре	This equipment is intended for use in ambient temperatures up to 40°C

# Refrigeration details

Refrigeration unit	Tropicalized and easy extractable monoblock unit to guarantee reliability and performance at 43°C. Equipped with low consumption electronic fan motors
Refrigerant charge	115 gr
Evaporator	Cataphoresis-treated for high corrosion resistance and installed external to compartment in order to ensure bigger loading capacity
Defrost	Automatic by hot gas for a shorter cycle and less thermal schocks
Condensate evaporation	Automatic through anti-corrosion treated compressor coil



# **Construction details**

Due divert dimensione WyDvII	702x810x2080
Product dimensions WxDxH	/UZX01UXZU0U
Packaging dimensions WxDxH	770x840x2190
Gross weight	122 Kg
Net weight	108 Kg
Structure	Stainless steel AISI 304 monocoque
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel
Insulation thickness	60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Inner corners	Rounded for an easy cleaning
Door	1 Self-closing door with 105° door stop. Right hinged, reversible on-site
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	In AISI 304 stainless steel, height adjustable (90mm-125mm)

# **Functions**

Control panel	Compact, simple and intuitive touch screen display
Open door alarm	Visual

#### **Accessories**

Lock	As standard
No. included accessories	3 - Plastic-coated grid GN 2/1530x650 mm 3 - Pair of runners for grid 530x650 mm (Mod. 700/1400)

#### **Versions**

Versions	Power supply frequency 60Hz