

Dynamic — TD2 P SP BT

Pastry and bakery



Technical data

| | |
|---------------------|-----------------------|
| Gross volume | 400 lt |
| Working temperature | -15-22 °C |
| Motor type | Plug-in |
| Refrigerant | R290 |
| Cooling power | 436 W (-25°C / +45°C) |
| Absorption | 556 W |
| Voltage/Frequency | 230V/1~/50Hz |
| Climate class | 5 / (40°C - 40%) |

Energy data (UE Reg. 2015/1094)

| | |
|------------|---|
| Net Volume | 269 lt |
| Type | This equipment is intended for use in ambient temperatures up to 40°C |

Refrigeration details

| | |
|------------------------|--|
| Refrigeration unit | Tropicalized and easy extractable monoblock unit to guarantee reliability and performance at 43°C. Equipped with low consumption electronic fan motors |
| Refrigerant charge | 80 gr |
| Evaporator | With cataphoresis anti-corrosion treatment |
| Defrost | Automatic by hot gas for a shorter cycle and less thermal shocks |
| Condensate evaporation | Automatic through anti-corrosion treated compressor coil |

Construction details

| | |
|----------------------------|---|
| Product dimensions WxDxH | 1440x800x860 |
| Packaging dimensions WxDxH | 1500x850x1000 |
| Gross weight | 119 Kg |
| Worktop | Without worktop |
| Structure | Stainless steel AISI 304 monocoque |
| External/Internal material | Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel |
| Insulation thickness | 60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP) |
| Inner corners | Rounded for an easy cleaning |
| Door | 2 Self-closing doors with 105° door stop, reversibles on site |
| Door gasket | Magnetic and removable, designed to improve insulation and to reduce energy consumption |
| Feet | AISI 304 stainless steel, height adjustable (135mm-230mm) |

Functions

| | |
|---------------|---|
| Control panel | High brightness touch screen display with 6 large digits. Tilted control panel |
| Functions | Three levels of ventilation intensity management, Led lighting ON/OFF, HACCP alarms through Ice connect (optional) |
| Connection | As optional: Remote access through serial interface. Via APP (only Android) it is possible to monitor HACCP traceability, appliance operation and parameters. Graphic and as CVS file export of registered data. Email sending of alarms notification |

Accessories

| | |
|--------------------------|---|
| Lighting | Optional |
| No. included accessories | 14 - Pair of runners for grid EN 600x400 mm |

Versions

| | |
|----------|-----------------------------|
| Versions | Power supply frequency 60Hz |
|----------|-----------------------------|